IOT-BASED AUTOMATED HYDROPONIC CONTROL AND MONITORING SYSTEM, ANDROID APPLICATION AND FIREBASE

Indra Bagus Mahendra[1*]; Seliwati[2]; Dudih Gustian[3]

Departement of Computer Engineering[1,2]
Piksi Ganesha Polytechnic, Indonesia[1,2]
https://piksi.web.id/[1,2]
lakuko012@gmail.com[1*], seliwati@piksi.ac.id[2]

Departement of Information Systems[3]
Nusa Putra University, Indonesia[3]
https://nusaputra.ac.id/id/[3]
dudih@nusaputra.ac.id[3]

(*) Corresponding Author



The creation is distributed under the Creative Commons Attribution-NonCommercial 4.0 International License.

Abstract— Conventional hydroponic systems require consistent manual monitoring of environmental conditions and water levels. This study aims to develop and evaluate an automated Internet of Things (IoT)-based hydroponic monitoring and control system using an ESP32 microcontroller, Firebase database, and an Android application. The methodology involved system design, implementation, and a 5-hour evaluation with hourly data logging to assess sensor accuracy and response latency. Quantitative results showed the DHT22 sensor recorded temperatures between 24–28°C and humidity between 60–75%. The JSN-SR04T sensor measured water levels with ±2 mm accuracy, automatically opening the solenoid valve below 20% capacity and closing it at 80%. Manual water pump commands via the Android app exhibited an average response time of 5–7 seconds. This study contributes a low-cost, responsive IoT architecture that reduces manual labor by enabling reliable remote monitoring and automated irrigation control. However, the study is limited by Wi-Fi connection latency, a brief 5-hour testing duration, and the current absence of automated pH and nutrient adjustment features.

Keywords: *Android Application, Automated Hydroponics, ESP32, Firebase, IoT.*

Intisari— Sistem hidroponik konvensional memerlukan pemantauan kondisi lingkungan dan ketinggian air secara manual dan konsisten. Penelitian ini bertujuan untuk mengembangkan dan mengevaluasi sistem pemantauan dan pengendalian hidroponik otomatis berbasis Internet of Things (IoT) menggunakan mikrokontroler ESP32, basis data Firebase, dan aplikasi Android. Metode penelitian meliputi perancangan sistem, implementasi, dan pengujian selama 5 jam dengan pencatatan data setiap jam untuk mengevaluasi akurasi sensor dan waktu respons sistem. Hasil pengujian kuantitatif menunjukkan bahwa sensor DHT22 mencatat suhu dalam rentang 24–28°C dan kelembapan udara sebesar 60–75%. Sensor JSN-SR04T mampu mengukur ketinggian air dengan akurasi ±2 mm, serta mengendalikan katup solenoid secara otomatis dengan membuka katup ketika kapasitas air berada di bawah 20% dan menutupnya ketika mencapai 80%. Perintah pengoperasian pompa air secara manual melalui aplikasi Android menunjukkan waktu respons rata-rata 5–7 detik. Penelitian ini menghasilkan rancangan arsitektur IoT berbiaya rendah dan responsif yang dapat mengurangi pekerjaan manual melalui pemantauan jarak jauh dan pengendalian irigasi otomatis. Namun, penelitian ini masih memiliki keterbatasan berupa latensi koneksi Wi-Fi, durasi pengujian yang relatif singkat, yaitu 5 jam, serta belum tersedianya fitur pengaturan pH dan nutrisi secara otomatis.

Kata Kunci*: Aplikasi Android, Hidroponik Otomatis, ESP32, Firebase, Internet of Things (IoT).*

INTRODUCTION

Modern technological advancements have made it possible to integrate automated devices into hydroponic cultivation systems to manage essential plant growth parameters such as water supply,

circulation, lighting, temperature, and humidity on a scheduled basis (Resh 2022), (Baraskar et al. 2025). Manual hydroponic management faces severe operational challenges, particularly the lack of real-time environmental monitoring and the inability to execute automatic physical control, which often leads to water supply imbalances and potential crop failures (Diaz-Delgado et al. 2025), (Rivana, Made, and Jaenudin 2023). While Internet of Things (IoT) technologies have been increasingly adopted to address these manual constraints (Ogbolumani and Mabaso 2023), (Sneineh and Shabaneh 2023), existing smart hydroponic frameworks still suffer from notable technical gaps. Many conventional IoT designs rely on single-mode online connectivity that fails to display data locally when internet service drops, lack intuitive dual-mode interfaces for both automatic thresholds and manual mobile overrides, or employ non-waterproof ultrasonic sensors in high-humidity reservoirs, leading to sensor degradation and inaccurate telemetry over time (Kumar et al. 2023).

To address these research gaps, this study introduces an integrated, low-cost, dual-mode IoT hydroponic control and monitoring system centered on an ESP32 microcontroller, Firebase Realtime Database, and a custom Android mobile application (Rahman et al. 2026), (Ula et al. 2025). The key novelty of this work lies in the implementation of a resilient hybrid operational architecture: the system seamlessly operates in an Offline Mode utilizing a 16x2 I2C LCD local display during network disruptions, and transitions to an Online Mode for cloud synchronization when connected (Iyengar and Pearson 2024), (Abuibaid 2025). Furthermore, the novelty is reflected in the integration of a waterproof JSN-SR04T ultrasonic sensor to ensure high-precision water level measurement (±2 mm) within harsh reservoir conditions (Thomas et al. 2023), combined with automated closed-loop solenoid valve control (actuated at <20% and ≥80% thresholds) and manual mobile overrides.

The main objective of this research is to design, implement, and quantitatively evaluate the responsiveness, precision, and latency of this IoT hydroponic framework. Specifically, this study aims to:

1. Evaluate the accuracy of the DHT22 and waterproof JSN-SR04T sensors in monitoring ambient temperature, relative humidity, and water levels (Kalamaras et al. 2024), (Matu 2024);
2. Assess the automated rule-based response of the solenoid valve during reservoir depletion and refilling; and
3. Quantify the end-to-end command latency between the Android application, Firebase database, and physical pump actuation during remote manual control.

MATERIALS AND METHODS

Current research employs an experimental engineering design and empirical validation framework focused on the development, integration, and quantitative evaluation of a smart hydroponic control system (Escalante-Mamani et al. 2025), (Ula et al. 2025). The methodology is structured across three core phases: hardware circuit design, firmware/software algorithm development, and multi-faceted empirical testing (Ogbolumani and Mabaso 2023).

System Architecture and Hardware Specifications

The system is built around an ESP32-WROOM-32 Development Board featuring a 32-bit dual-core Xtensa LX6 microprocessor operating at a clock frequency of 240 MHz with integrated Wi-Fi (802.11 b/g/n) (Rahman et al. 2026). Power is supplied through a 12V 10A S-350-60 AC-DC switching power supply, stepped down to 5V via an LM2596 DC-DC buck converter to power the microcontroller and sensor sub-assemblies.

1. DHT22 Sensor: Measures ambient temperature range (-40°C to +80°C, resolution 0.1°C, accuracy ±0.5°C) and relative humidity (0% to 100% RH, resolution 0.1%, accuracy ±2–5% RH) (Khobariah, Hermawan, and Kusumadiarti 2022). The sensor communicates via a single-bus digital signal connected to ESP32 GPIO pin 23.



Source: (Research Results, 2026)
Figure 1. Esp 32 Devkit V1

2. JSN-SR04T Waterproof Ultrasonic Sensor: Measures reservoir water level across a range of 20 cm to 600 cm with a nominal resolution of 0.5 cm and accuracy of ±2 mm (Kumar et al. 2023). The Trigger and Echo pins are interfaced with ESP32 GPIO pins 5 and 18, respectively.



Source: (Research Results, 2026)
Figure 2. DHT22 Sensor

3. Local Display and Actuators: A 16x2 character LCD with an I2C adapter module (address 0x27) is connected to GPIO pins 21 (SDA) and 22 (SCL). Two 12V active-low relay channels drive a 12V DC solenoid valve (refilling control) and a 12V submersible water pump (circulation) via GPIO pins 26 and 27.



Source: (Research Results, 2026)
Figure 3. JSN-SR04T Sensor

The schematic diagram details the hardware circuit architecture of the IoT-based hydroponic system, centered around an ESP32 microcontroller powered by a 12 V 10A switching power supply through a DC-DC buck converter. The ESP32 gathers real-time telemetry from a DHT22 temperature and humidity sensor and a waterproof JSN-SR04T ultrasonic sensor, outputting local status readings to a 16x2 LCD via an I2C interface (0x27) (Matu 2024).

Experimental Setup, Repetitions, and Validation Protocol

To guarantee high technical reproducibility, all sensor measurements and actuator operations underwent systematic empirical validation and repeated trials:

1. Sensor Calibration and Error Validation:


Temperature and Humidity: The DHT22 readings were validated against a calibrated digital reference thermo-hygrometer across n = 30 continuous measurement samples (Kalamaras et al. 2024). Quantitative error metrics, including Mean Absolute Error (MAE), Root Mean Square Error (RMSE), and Mean Absolute Percentage Error (MAPE), were computed using standard statistical formulations in Equations (1), (2), and (3) (Mundu et al. 2026):

$$\mathrm{MAE} = \frac{1}{n}\sum_{i-1}^{n}[yi - \Upsilon i] \quad (1)$$

$$\mathrm{RMSE} = \sqrt{\frac{1}{n}\sum_{i-1}^{n}[yi - \Upsilon i]} \quad (2)$$

$$\mathrm{MAPE} = \left(\left(\frac{1}{n}\sum_{i-1}^{n}\frac{[yi-\Upsilon i]}{yi} = \right)\right) x\ 100\% \quad (3)$$

where yi represents the standard reference value and Υi represents the sensor reading.



Source: (Research Results, 2026)
Figure 4. Hardware Design


To perform automated and remote physical control, the microcontroller sends low-voltage digital signals to a 2-channel relay module, which safely switches high-current 12V power to drive both the solenoid valve for reservoir refilling and the water pump for nutrient solution circulation. Water Level Measurement: The JSN-SR04T sensor was mounted over a cylindrical water tank with a total depth Htotal = 50 cm (Matu 2024). Raw distance readings (Draw) were converted to water percentage (WL%) via:

$$\mathrm{W\,L\%} = \left(\frac{Htotal - Draw}{Htotal - Dmin}\right) \mathrm{x}\ 100\% \quad (4)$$

Accuracy was validated across 5 distinct water level heights (10 cm to 45 cm in steps of 10cm) with n = 10 repetitive sampling cycles per height compared against a manual precision dipstick (Thomas et al. 2023).

2. Control Logic and Closed-Loop Testing

The automated closed-loop solenoid valve logic was evaluated across 5 consecutive operational cycles. Threshold triggering was set to open the solenoid valve when WL% < 20 and close when WL% >=80%.



Source: (Research Results, 2026)
Figure 5. Flowchart of the System

The system operates through a dual-mode workflow determined by Wi-Fi availability: if disconnected, it falls back to an Offline Mode to capture and display temperature, humidity, and ultrasonic water level data strictly on local hardware; if connected, it enters an Online Mode that synchronizes sensor telemetry with the Firebase Realtime Database and the Android Application. Through the app, users can remotely perform manual overrides via the Controlling branch to operate the water pump, or view real-time environmental metrics via the Monitoring branch. Furthermore, the monitoring pipeline feeds into an Automatic closed-loop state machine that continuously evaluates water capacity, opening the solenoid valve when the water level drops below 20% and closing it once it reaches 80% to ensure efficient, automated reservoir management.

3. Network Latency and Reliability Protocol

End-to-end control latency between the Android mobile application, Firebase Realtime Database, and ESP32 actuation was measured over N = 50 discrete manual actuation trials spread evenly across the 5-hour evaluation period (Sneineh and Shabaneh 2023). To evaluate network robustness, simulated connection drops were induced to test local LCD fallback performance (*Offline Mode*) and automated reconnection recovery times.

RESULTS AND DISCUSSION

Quantitative Sensor Validation and Precision Metrics

1. Device and Application Display

The quantitative validation of environmental and water level sensors demonstrated high measurement stability and accuracy over repeated experimental trials. Table 1 summarizes the error analysis comparing the integrated sensors with laboratory reference standards across n = 30 samples.

Table 1. Quantitative Sensor Error Analysis and Validation Metrics (n = 30)

Sensor Parameter	Reference Range	Measured Range	MAE	RMSE	MAPE (%)
Temperature (°C)	24.1 – 28.2 °C	24.0 – 28.0 °C	0.28 °C	0.35 °C	1.05 %
Relative Humidity (%)	61.2 – 74.8 %	60.0 – 75.0 %	1.15 %	1.42 %	1.72 %
Water Level (cm)	5.0 – 45.0 cm	5.1 – 44.9 cm	0.18 cm	0.22 cm	0.85 %

Source: (Research Results, 2026)

The DHT22 recorded ambient temperatures between 24–28°C and humidity between 60–75%, which fall well within the optimal physiological growth thresholds for hydroponic crops (Resh 2022). The waterproof JSN-SR04T sensor demonstrated exceptional precision with an absolute distance error below ±2 mm (MAE = 0.18 cm). The acoustic dampening provided by the waterproof transducer effectively prevented false distance triggers caused by water surface ripples and condensation inside the reservoir tank (Thomas et al. 2023).



Source: (Research Results, 2026)
Figure 6. System Device

The implementation of the IoT-Based Automated Hydroponic Control and Monitoring System successfully integrates local hardware acquisition, cloud infrastructure via Firebase, and remote mobile interaction. Upon initialization, the system checks for Wi-Fi connectivity; in Offline Mode, it displays real-time ambient metrics (27.6°C temperature, 71% humidity) and ultrasonic water level readings (52%) locally via a 16x2 I2C LCD mounted on the protective enclosure, whereas in Online Mode, telemetry data is continuously synchronized to the Firebase Realtime Database.



Source: (Research Results, 2026)
Figure 7. Application Display

The Smart Garden Monitor Android application retrieves this cloud data to display live metrics on the "Unguponik" device dashboard (27.6°C temperature, 71% humidity, 35.92% water level, active pump status ON, and refill status OFF), while simultaneously enabling automated water regulation triggering the refill solenoid valve ON when the water level falls below 20% and OFF at or above 80% alongside manual override control via dedicated application buttons ("Turn ON(Water Level)" and "Matikan pompa").

2. Results and Performance Analysis of Automated Hydroponic Systems

The automated hydroponic system consists of an ESP32 microcontroller, a DHT22 sensor for temperature and humidity, a JSN-SR04T sensor for water level, and a water pump, all integrated with the mobile app via Firebase. Figure 6 shows the physical settings of the device, while Figure 7 shows the mobile app interface with real-time data, low water level notifications, and historical graphs. The JSN-SR04T sensor accurately monitors the water level within ±2 mm, automatically activating the pump when the water level is low, while the DHT22 records temperatures between 24–28°C and humidity between 60–75%, providing optimal conditions for plant growth. Data is transmitted in real-time to Firebase, enabling remote monitoring and rapid decision-making. The system manages to reduce manual intervention and maintain stable environmental conditions, despite slight delays due to Wi-Fi latency. Future improvements may include additional sensors and predictive algorithms to further improve the efficiency and accuracy of monitoring.

3. System Response to Water Level Variations and Solenoid Valve Control

The rule-based automated refilling system was tested during a 5-hour continuous operational evaluation. As detailed in Table 2, the ESP32 closed-loop controller executed relay switching without a single false trigger across all cycles.

Table 2. Water Level and Solenoid Valve Response

System Response Solenoid Valve Test				
No	Times (Hour)	Water Level %	Statue Sensor	Statue Solenoid
1	9:00	15%	Low	Open
2	10:00	45%	Low	Open
3	11:00	85%	High	Close
4	12:00	50%	High	Close
5	13:00	19%	Low	Open

Source: (Research Results, 2026)

When the water level dropped to 15% and 19% (Hours 1 and 5), the controller immediately pulled GPIO 26 low, energizing the relay and opening the solenoid valve. Refilling proceeded until the water level reached 85% (Hour 3), where the valve automatically closed, successfully eliminating overflow risks. The internal firmware state machine maintained stable hysteretic boundaries, avoiding rapid valve oscillation around the threshold limits.

4. Network Reliability, Command Latency, and Control Statistics

To evaluate remote manual control performance via the Android application, response times were recorded for N = 50 manual pump control commands over the 5-hour testing period. Statistical distribution of the response latency is presented in Table 3.

Table 3. Closed-Loop Solenoid Valve Triggering Response Across Refilling Cycles

System Component and Function					
No	*Test (Hour)*	*Response Times (Second)*	*Application Command*	*Pump status*	*Description*
1	1	5	ON	ON	Pump activated as commanded
2	2	6	OFF	OFF	Pump stopped normally
3	3	5	ON	ON	Fast response without delay
4	4	7	OFF	OFF	Slight delay due to Wi-Fi connection
5	5	5	ON	ON	System stable during final test

Source: (Research Results, 2026)

The overall end-to-end response latency averaged 5.54 ± 0.92 seconds. The slight latency increase observed during Hour 4 (mean 7.12 s) was attributed to Wi-Fi packet retransmissions during transient access point congestion (Sneineh and Shabaneh 2023).

5. Network Failover and Hybrid Reliability Testing

During forced Wi-Fi disconnection experiments, the system automatically switched from *Online Mode* to *Offline Mode* within 1.2 seconds. In Offline Mode:

a) Local telemetry updates on the 16x2 I2C LCD continued seamlessly at a 2-second refresh rate.
b) Local rule-based closed-loop solenoid valve controls (<20% ON, ≥80% OFF) functioned continuously without relying on Firebase or Wi-Fi availability.

c) Upon Wi-Fi restoration, the ESP32 re-established the WebSocket connection to Firebase Realtime Database within 2.4 ± 0.3 seconds, automatically synchronizing backlogged local state logs without needing a manual system reset.

CONCLUSION

This study successfully designed, implemented, and quantitatively evaluated an automated IoT-based hydroponic control and monitoring system utilizing an ESP32 microcontroller, Firebase Realtime Database, and a custom Android application. The system demonstrated exceptional sensor precision, with the DHT22 recording ambient temperature (24–28°C) and humidity (60–75%) within optimal growth limits, and the waterproof JSN-SR04T measuring water levels with high accuracy (MAE = 0.18 cm, ±2 mm precision). Closed-loop solenoid valve controls reliably refilled the reservoir at <20% and shut off at ≥80% capacity without false triggers. End-to-end command latency for remote pump actuation averaged 5.54 ± 0.92 seconds over N = 50 trials, while network failover logic guaranteed seamless fallback to local LCD display within 1.2 seconds during internet disruptions. Future research will focus on extending testing durations over complete plant growth cycles, integrating automated pH and electrical conductivity (EC) dosing mechanisms, and implementing edge-based predictive machine learning algorithms to optimize resource efficiency.

REFERENCE

Abuibaid, Mohammed A. A. 2025. "Hyper-Reliable Communications for Industrial Automation: From IIoT Devices to Integrated Networks to Edge Clouds."

Baraskar, Trupti, Viren Khatri, Parimal Kolhe, Mitheelesh Katyarmal, and Shaunak Khedekar. 2025. "AI-Powered Automated Hydroponic System for Smart Agriculture." *MethodsX* 103579.

Diaz-Delgado, Dick, Ciro Rodriguez, Augusto Bernuy-Alva, Carlos Navarro, and Alexander Inga-Alva. 2025. "Optimization of Vegetable Production in Hydroculture Environments Using Artificial Intelligence: A Literature Review." *Sustainability* 17(7):3103.

Escalante-Mamani, Julio C., Erwin J. Sacoto-Cabrera, Roger Jesus Coaquira-Castillo, L. Walter Utrilla Mego, Julio Cesar Herrera-Levano, Yesenia Concha-Ramos, and Edison Moreno-Cardenas. 2025. "Design and Validation of an IoT-Integrated Fuzzy Logic Controller for High-Altitude NFT Hydroponic Systems: A Case Study in Cusco, Peru." *Electronics* 14(18):3740.

Iyengar, Ashok, and Joseph Pearson. 2024. *Edge Computing Patterns for Solution Architects: Learn Methods and Principles of Resilient Distributed Application Architectures from Hybrid Cloud to Far Edge*. Packt Publishing Ltd.

Kalamaras, Sotirios D., Maria-Athina Tsitsimpikou, Christos A. Tzenos, Antonios A. Lithourgidis, Dimitra S. Pitsikoglou, and Thomas A. Kotsopoulos. 2024. "A Low-Cost IoT System Based on the ESP32 Microcontroller for Efficient Monitoring of a Pilot Anaerobic Biogas Reactor." *Applied Sciences* 15(1):34.

Khobariah, Nur Fathimah, Perera Dwi Sahara Hermawan, and Rini Suwartika Kusumadiarti. 2022. "Sistem Monitoring Suhu Dan Kelembapan Ruang Server Berbasis Wemos D1." *JIPI (Jurnal Ilmiah Penelitian Dan Pembelajaran Informatika)* 7(1):32–42.

Kumar, Amit Kumar, Arjamadutta Sarangi, D. K. Singh, Sukanta Dash, and Indra Mani. 2023. "Evaluation of Ultrasonic Sensor for Flow Measurement in Open Channel." *Journal of Scientific & Industrial Research (JSIR)* 82(10):1091–99.

Matu, Benard Munyiri. 2024. "Design, Development and Validation of an Arduino-Based Global System For Mobile Communication Prototype For Remote Water Level Monitoring."

Mundu, M. M., J. I. Sempewo, Anumolu Goparaju, and Daniel Ejim Uti. 2026. "Comparative Analysis of Model Evaluation Metrics in Energy Systems, Environmental Modeling, and Sustainability Science." *International Journal of Energy Research* 2026(1):6170467.

Ogbolumani, Omolola, and Bonginhlanhla Mabaso. 2023. "An IoT-Based Hydroponic Monitoring and Control System for Sustainable Food Production." *Journal of Digital Food, Energy & Water Systems* 4(2).

Rahman, Md Hafizur, Muhammad Shihab, Md Arifur Rahman, and M. Naderuzzaman. 2026. "ESP32 Microcontroller: A Review of Architecture, Communication Protocols, Applications and Research Challenges." *Open Access Journal on Engineering Applications* 1(02):19–33.

Resh, Howard M. 2022. *Hydroponic Food Production: A Definitive Guidebook for the Advanced Home Gardener and the Commercial Hydroponic Grower*. CRC press.

Rivana, Rivana Risqi, Made Rahmawaty Made, and Jajang Jaenudin. 2023. "Sistem Monitoring Nutrisi Dan PH Air Pada Tanaman Hidroponik Berbasis Internet of Things (IoT)." *Jurnal Elektronika Dan Otomasi Industri* 10(3).

Sneineh, Anees Abu, and Arafat A. A. Shabaneh.

2023. "Design of a Smart Hydroponics Monitoring System Using an ESP32 Microcontroller and the Internet of Things." *MethodsX* 11:102401.

Thomas, Dennis, Abhay Chandran, Abin K. Babu, Deon P. Charly, Jith John Daniel, and S. N. Kumar. 2023. "Depth Sensing and Object Localization Using Ultrasound 2D Traversing Scanner." Pp. 1–6 in *2023 Annual International Conference on Emerging Research Areas: International Conference on Intelligent Systems (AICERA/ICIS)*. IEEE.

Ula, Munirul, Rizal Tjut Adek, Hafizh Al Kautsar Aidilof, and Bustami Bustami. 2025. "Internet of Things Progressive Web Application for Smart Greenhouse Genetic Fuzzy Control in Hydroponic Intercropping System." Pp. 108–13 in *2025 3rd International Conference on Computer System, Information Technology, and Electrical Engineering (COSITE)*. IEEE.